

WE 24-230 MVT (606469390) Angle grinder (110-120 V / 50 - 60 Hz); Cardboard box; with rotating main handle

Order no. 606469390 EAN 4007430265289



Product may differ from Image











- Metabo Marathon motor with patented dust protection for long service life
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Deadman's switch for high user protection
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	230 mm // 9 "
Rated input power	2300 W
Output power	1600 W
No-load speed	6600 rpm
Speed at rated load	4600 rpm
Torque	17 Nm / 150 in-lbs
Spindle thread	M 14
Handle circumference	144 mm / 5.669 "
Weight (without power cable)	5.8 kg / 12.8 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6.2 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	2.5 m/s²
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Flat-pin spanner

Inner support flange

Nut with two holes

www.metabo.com 2/2