

NP 23 700616

Key features	
Needles ø 3 mm	19 pcs. pointed
Air consumption	100 I/min, 3.5 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	5.48 m/s ²
Sound pressure level	< 100.7 db(A)
Acoustic power level	< 110.0 db(A)

Packaging



Case size 475×360×110 mm / 18.7×14.1×4.3"

Field of application

The unit is intended for machining the surfaces of metal, concrete and stone for the purposes of cleaning, derusting, roughening, descaling, clearing, smoothing and bush-hammering.

Physical parameters	
Weight	2.6 kg / 5.7 lbs
Connection thread	G 3/8"

One case contains		
NP 23 needle scaler		
Hose connection G3/8 × 10 mm		
VAC Connector		
Auxiliary handle		
2 pcs. of piston seals		
Tube of grease		
Operating manual		

Recommended lubricants		
ВР	Energol RD-E46	
Mobil	Almo Oil 325	
Shell	Torcula 100	
DEA	Arkas 32	
Texaco	Aries 32	
Esso	Arox EP 46 or EP 100	



Set needles compl.	ø 2 mm. blunt	ø 3 mm. blunt	ø 3 mm. pointed	ø 4 mm. blunt	ø 4 mm. pointed
Article code	706187	706188	706189	706190	706191

Blunt	0
Pointed	

