



# DK 1 H

## 700763

### Key features

Multipurpose tools that allow to create a natural and smooth roughening effect on all surfaces

Applicable for processing concrete, stone and granite surfaces

Removal of different overlays on concrete as laitance, colors and encrustations

Can be used on vertical surfaces and in restricted areas

### Technical data

Air consumption	160 L / Min. (5.7 cfm)
Max. permitted air pressure	7 bar (100 psi)
Vibration value on handle	13.7 m / s <sup>2</sup>
Sound pressure level	≤ 86.7 db(A)
Acoustic power level	≤ 94.7 db(A)
Connection thread	G 3/8"

### Field of application

Quickly removes laitance, projections, encrustation, scale deposits, colour, smoothes roughening and much more.

### Standards

#### EC Machinery Directive 2006 / 42 / EC

The units (DK 1 H - 3 H) had been constructed in accordance with the state of the art and the safety requirements of European Standard

**EN ISO 11148-4:2013** (Hand-Held, Non-Electrically Operated Machinery).

### Physical parameters

Weight	3.1 kg / 6.8 lbs
Length	620 mm / 24"

## Spare parts

**Pistons with tungsten crown for DK 1 H**

Pistons set  
**700769**



**One set contains:** 1 Piston with tungsten crown - 0.36 kg / 0.79 lbs